

MECHES METAL / METAALBOREN

DORMER

Ref. VV

Embl/verp

Ref. VV

Embl/verp

MECHES CYLINDRIQUES

A100

SPIRAALBOREN

HSS DIN 338

| | Ø mm | |
|-----|------|----|
| 758 | 0.35 | 10 |
| 759 | 0.40 | 10 |
| 760 | 0.50 | 10 |
| 761 | 0.60 | 10 |
| 762 | 0.70 | 10 |
| 763 | 0.75 | 10 |
| 764 | 0.80 | 10 |
| 765 | 0.90 | 10 |
| 728 | 1 | 10 |
| 766 | 1.10 | 10 |
| 767 | 1.20 | 10 |
| 768 | 1.25 | 10 |
| 769 | 1.30 | 10 |
| 770 | 1.40 | 10 |
| 729 | 1.50 | 10 |
| 771 | 1.60 | 10 |
| 772 | 1.70 | 10 |
| 773 | 1.75 | 10 |
| 774 | 1.80 | 10 |
| 775 | 1.90 | 10 |
| 730 | 2 | 10 |
| 776 | 2.10 | 10 |
| 777 | 2.20 | 10 |
| 778 | 2.25 | 10 |
| 779 | 2.30 | 10 |
| 780 | 2.40 | 10 |
| 731 | 2.50 | 10 |
| 781 | 2.60 | 10 |
| 782 | 2.70 | 10 |
| 783 | 2.75 | 10 |
| 784 | 2.80 | 10 |
| 785 | 2.90 | 10 |
| 732 | 3 | 10 |
| 786 | 3.10 | 10 |
| 787 | 3.20 | 10 |
| 788 | 3.25 | 10 |
| 789 | 3.30 | 10 |
| 790 | 3.40 | 10 |
| 733 | 3.50 | 10 |
| 791 | 3.60 | 10 |
| 792 | 3.70 | 10 |
| 793 | 3.75 | 10 |
| 794 | 3.80 | 10 |
| 795 | 3.90 | 10 |

| | Ø mm | |
|-----|-------|----|
| 734 | 4 | 10 |
| 796 | 4.10 | 10 |
| 797 | 4.20 | 10 |
| 798 | 4.25 | 10 |
| 799 | 4.30 | 10 |
| 800 | 4.40 | 10 |
| 735 | 4.50 | 10 |
| 801 | 4.60 | 10 |
| 802 | 4.70 | 10 |
| 803 | 4.75 | 10 |
| 804 | 4.80 | 10 |
| 805 | 4.90 | 10 |
| 736 | 5 | 10 |
| 806 | 5.10 | 10 |
| 807 | 5.20 | 10 |
| 808 | 5.25 | 10 |
| 737 | 5.50 | 10 |
| 809 | 5.75 | 10 |
| 810 | 5.80 | 10 |
| 738 | 6 | 10 |
| 812 | 6.10 | 10 |
| 811 | 6.20 | 10 |
| 813 | 6.40 | 10 |
| 739 | 6.50 | 10 |
| 814 | 6.80 | 10 |
| 740 | 7 | 10 |
| 816 | 7.20 | 10 |
| 741 | 7.50 | 10 |
| 742 | 8 | 10 |
| 817 | 8.20 | 10 |
| 743 | 8.50 | 10 |
| 744 | 9 | 10 |
| 745 | 9.50 | 10 |
| 746 | 10 | 10 |
| 747 | 10.50 | 5 |
| 748 | 11 | 5 |
| 749 | 11.50 | 5 |
| 750 | 12 | 5 |
| 751 | 12.50 | 5 |
| 752 | 13 | 5 |
| 753 | 13.5 | 1 |
| 754 | 14 | 1 |
| 755 | 14.50 | 1 |
| 756 | 15 | 1 |
| 757 | 16 | 1 |

Type A100



MECHES TITANE

A002

TIN BOREN

très résistante, diminue les frottements
et augmente la vitesse de coupe.

extra weerstand tegen slijtage, verlaagt wrijvingsweerstand
en biedt de mogelijkheid om de snijsnelheden te verhogen.

| | Ø mm | |
|-----|------|----|
| 821 | 1 | 10 |
| 822 | 1,5 | 10 |
| 823 | 2 | 10 |
| 824 | 2,5 | 10 |
| 825 | 3 | 10 |
| 826 | 3,5 | 10 |
| 827 | 4 | 10 |
| 828 | 4,5 | 10 |
| 829 | 5 | 10 |
| 830 | 5,5 | 10 |
| 831 | 6 | 10 |
| 832 | 6,5 | 10 |
| 833 | 7 | 10 |
| 865 | 7,5 | 10 |
| 834 | 8 | 10 |
| 866 | 8,5 | 10 |
| 835 | 9 | 10 |
| 867 | 9,5 | 10 |
| 836 | 10 | 10 |
| 868 | 10,5 | 5 |
| 869 | 11 | 5 |
| 870 | 11,5 | 5 |
| 837 | 12 | 5 |
| 838 | 12,5 | 5 |
| 839 | 13 | 5 |



COFFRETS

BORENSETS

| | | | |
|-----|----------|----|--------------|
| 874 | A095-201 | 19 | 1-10mm x 0,5 |
| 875 | A095-204 | 25 | 1-13mm x 0,5 |



TARAUDS MACHINE

MACHINETAPPEN

Rectifiés et détalonnés

Geslepen en achtergeslepen

Acier HSS

HSS staal

Finisseur n°3

Afwerker nr.3

| | | |
|-----|------|------------|
| 880 | E500 | M3x0,50mm |
| 881 | E500 | M4x0,70mm |
| 882 | E500 | M5x0,80mm |
| 883 | E500 | M6x1,00mm |
| 884 | E500 | M8x1,25mm |
| 885 | E500 | M10x1,50mm |
| 886 | E500 | M12x1,75mm |



HUILES DE COUPE

SNIJOLIE

| | | | |
|-----|--------|-----------------------------|--------|
| 905 | M200-1 | Acier/Staal | 0.25 l |
| 906 | M200-2 | Aluminium | 0.25 l |
| 918 | M200-3 | Sans chlore / Chloorvrij | 0.25 l |
| 907 | M200 | spray | 400ml |

